

# Microsemi Adaptec® SmartHBA 2100 Series: 2100-24i/8i8e/8i/4i4e

## 12 Gbps PCIe Gen3 SAS/SATA Host Bus Adapter with Basic Hardware RAID

### Smart Storage, Connectivity, and Hardware RAID

Today's data centers and enterprises need storage solutions that can keep pace with rapid data expansion. The SmartHBA 2100 Series is the newest product in the Smart Storage solutions family, forged through the convergence of Microsemi SAS/SATA protocol controller expertise, more than 30 years of Microsemi board innovation, and the new Smart Storage stack.

The SmartHBA 2100 series, available in three different 12 Gbps configurations with up to 24 ports, uniquely combines the capabilities of a full-featured host bus adapter (HBA) like the HBA 1100 with those of a basic RAID adapter using hardware RAID. With an optimal mix of resiliency, efficiency, and ease of use, it adds the robustness of true host-offloading hardware RAID, offers open-source driver compatibility, and comes with a full set of storage management tools. The SmartHBA 2100 Series offers the flexibility of internal and external connectivity in a low-profile/MD2 form factor.

### Resiliency, Efficiency, and Data Availability

The SmartHBA 2100 is an ideal solution for server-based storage systems that require maximum bandwidth and I/O connectivity, low power consumption, high reliability, plus options for data availability. The Smart Software stack even allows a combination of RAID and raw devices. This is useful in SDS environments where hardware RAID significantly increases OS boot reliability, but full HBA features and performance are otherwise needed. The SmartHBA 2100 also provides enhanced enclosure management capabilities to both RAID and raw devices, and enables enclosure services by providing a virtual SEP to software stacks if needed.<sup>1</sup>

The SmartHBA 2100 offers over 40 percent power savings compared to prior generations and significant power advantages versus competing solutions, giving it the lowest total cost of ownership (TCO) for an HBA/basic RAID solution. It delivers a robust and scalable solution that can handle the toughest system workloads and configurations, from an array of high-performance SSDs to high-capacity HDDs. The 2100 can be used with or without SAS expanders.

### Maximum Performance


The SmartHBA 2100 series provides the highest levels of storage performance and scalability for next-generation data centers. The SmartHBA 2100 provides connectivity to large numbers of storage devices, including HDDs, SSDs, and SMR drives. These storage devices can aggregate the performance of devices to the limits of the PCIe Gen3 host bus at 6.6 Gbps, and achieve up to 1.7M IOPS and 60 percent higher IOPS performance with SATA devices without additional overhead or latency.<sup>2</sup>

### Entry-Level RAID Functionality

The SmartHBA 2100 combines uncompromised HBA functionality with basic RAID support in hardware using the Microsemi PM8222 SmartIOC 2100 silicon. Robust RAID support is the same for all platforms and operating systems, providing a consistent user experience. Metadata compatibility with SmartRAID 3100 products allows customers to upgrade to a full-featured hardware RAID solution with caching for acceleration if needed. The SmartHBA 2100 supports up to 32 hard disk drives or SSDs in RAID configurations using RAID levels 0, 1, 10, or even RAID 5, and can simultaneously use RAID arrays and raw devices in mixed mode.

### Unified Microsemi Storage Management Utilities

maxView provides both server and remote administration, including proactive failure notification, and supports all Microsemi HBA, SmartHBA, and SmartRAID products, including backward compatibility. This browser-based tool suite supports all standard browsers, and is also available as an offline USB boot image. maxView adapter management components include the maxView GUI, an ARCCONF command-line tool, an event monitor for logging and email alerts, a CIM provider, and a vSphere plugin.



### Benefits

- Ideal for high-performing I/O solutions supporting SAS/SATA HDDs and SSDs requiring maximum connectivity
- Combines full HBA functionality with basic hardware RAID
- Offers basic RAID functionality for up to 32 devices supporting RAID levels 0, 1, 10, and 5 in conjunction with full HBA functionality for up to 238 devices
- Broad operating system support through highly efficient, low-latency PQIDriver driver (fully open-source for Linux/FreeBSD)
- Performance of up to 1.7M random read IOPS with extremely low-latency 4 KB I/Os

### Highlights

- Up to 24 native SAS/SATA ports; low-profile MD2 form factor
- 12 Gbps SAS data rates using mini-SAS HD connectors
- Basic hardware RAID plus full-featured high-performance HBA in the same solution
- Significant power savings delivers lowest total cost of ownership versus competing solutions
- The unified maxView management tools and drivers across the Microsemi HBA, RAID, and expander solutions enable easy manageability across the entire product line
- Proven compatibility with existing Microsemi Adaptec solutions, multiple operating systems, servers, enclosures, SSDs, HDDs, and LTO tape drives
- Uses the latest 28nm SmartIOC 2100 SAS/SATA protocol controller to drive efficiency and performance while also having the industry's lowest power consumption
- Quality and reliability through the unified, hardened Smart Storage stack, which is deployed in over 30M servers

<sup>1</sup> Provides a virtual SES processor to the host OS/SDS stack for passive backplanes with SGPIO/IBPI support.

<sup>2</sup> 16- and 24-port adapters can achieve 1.7M random read IOPS for 4 KB I/Os. Adapters with 8 ports and fewer are capable of 1.5M IOPS.

# Microsemi Adaptec® SmartHBA 2100 Series: 2100-24i/8i8e/8i/4i4e

## 12 Gbps PCIe Gen3 SAS/SATA Host Bus Adapter with Basic Hardware RAID

### Parameters

| Parameter                | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Key software features    | <ul style="list-style-type: none"> <li>Support for up to 256 SAS/SATA target devices (238 SSD/HDDs maximum support and remainder are reserved for expanders and enclosure management)</li> <li>Support for up to 32 drives in RAID arrays</li> <li>Hardware RAID level 0,1,10,5 support</li> <li>Multi-LUN support</li> <li>SAS expander support</li> <li>TLR</li> <li>SATA NCQ</li> <li>Hot plug drive support</li> </ul> <ul style="list-style-type: none"> <li>S.M.A.R.T.</li> <li>MPIO support</li> <li>Multi-initiator (host)/clustering for SAS (HBA devices only)</li> <li>Enclosure management</li> <li>SES-2, SES-3</li> <li>SFF-8485, SGPIO</li> <li>SFF-8489, IBPI</li> <li>BMC support</li> </ul>                                                                                                                                                                                                                                                                                                                     |
| Management utilities     | <p><b>maxView Storage Manager</b></p> <ul style="list-style-type: none"> <li>Web-based GUI management utility</li> <li>OS support: Windows, Linux, Solaris, VMware</li> <li>Remote configuration, monitoring, and notification</li> <li>Remote firmware updates</li> <li>SMI-S support</li> <li>SMTP</li> </ul> <p><b>ARCCONF</b></p> <ul style="list-style-type: none"> <li>Command-line interface</li> <li>SMI-S support for VMware</li> </ul> <p><b>BIOS Configuration Utility (CTRL+A)</b></p> <ul style="list-style-type: none"> <li>Legacy configuration utility</li> <li>Flashable BIOS support</li> </ul> <p><b>ROM-based uEFI BIOS Configuration Utilities</b></p> <ul style="list-style-type: none"> <li>HLI-based pre-boot GUI configuration utility</li> <li>Arccconf CLI for uEFI shell</li> <li>Flashable BIOS support</li> </ul> <p><b>Event Monitor</b></p> <ul style="list-style-type: none"> <li>Lightweight event monitoring and logging tool</li> <li>Distributes adapter events and notifies user</li> </ul> |
| Operating systems        | Microsoft Windows Server, Windows 10, Windows 8.1, Windows 7, Red Hat Enterprise Linux, CentOS, SuSE Linux Enterprise Server, Ubuntu Linux, Debian Linux, Oracle Linux, Citrix XenServer, Solaris, FreeBSD, VMware ESXi, and open-source Linux drivers. The latest drivers and OS support are at <a href="http://storage.microsemi.com/en-us/support/start">storage.microsemi.com/en-us/support/start</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| CPU architecture         | Intel, AMD, Cavium ThunderX2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Physical dimensions      | 2.535" H x 6.6" L (64 mm x 167 mm) or all SKUs except the SmartHBA 2100-4i4e, which is 2.535" H x 5.2" L (64 mm x 132.08 mm)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Operating temperature    | 50 °C ambient and 55 °C with 200 LFM airflow.<br><b>Note:</b> This adapter contains a powerful I/O processor that requires adequate airflow to operate reliably. Please install this card only into server or PC chassis with at least 200 LFM airflow. Temperature measured 1 inch from adapter.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Regulatory certification | CE, FCC, UL, C-tick, VCCI, KCC, CNS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Environmental compliance | RoHS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Warranty                 | 3 years                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Accessories              | Serial Attached SCSI (SAS) cables ( <a href="http://www.microsemi.com/product-directory/storage-boards/3686-cables-accessories">www.microsemi.com/product-directory/storage-boards/3686-cables-accessories</a> )                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

### Ordering Information

| SmartHBA 2100 Series | Part Number | Host Interface    | Form Factor      | SAS/SATA Ports         | Connectors                      | MTBF        | RAID Levels | Caching |
|----------------------|-------------|-------------------|------------------|------------------------|---------------------------------|-------------|-------------|---------|
| SmartHBA 2100-24i    | 2301600-R   | 8-Lane PCIe Gen 3 | Low-profile, MD2 | 24 internal            | 6 (x4) SFF-8643                 | 2.73M hours | 0, 1, 10, 5 | N/A     |
| SmartHBA 2100-8i8e   | 2301900-R   |                   |                  | 8 internal/ 8 external | 2 (x4) SFF8644/ 2 (x4) SFF-8643 | 2.0M hours  |             |         |
| SmartHBA 2100-8i     | 2290400-R   |                   |                  | 8 internal             | 2 (x4) SFF-8643                 | 1.36M hours |             |         |
| SmartHBA 2100-4i4e   | 2292200-R   |                   |                  | 4 internal/ 4 external | 1 (x4) SFF8644/ 1 (x4) SFF-8643 | >1.4M hours |             |         |



#### Microsemi Headquarters

One Enterprise, Aliso Viejo, CA 92656 USA  
 Within the USA: +1 (800) 713-4113  
 Outside the USA: +1 (949) 380-6100  
 Sales: +1 (949) 380-6136  
 Fax: +1 (949) 215-4996  
 email: [sales.support@microsemi.com](mailto:sales.support@microsemi.com)  
[www.microsemi.com](http://www.microsemi.com)

Microsemi, a wholly owned subsidiary of Microchip Technology Inc. (Nasdaq: MCHP), offers a comprehensive portfolio of semiconductor and system solutions for aerospace & defense, communications, data center and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; enterprise storage and communication solutions, security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Learn more at [www.microsemi.com](http://www.microsemi.com).

Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.

©2018 Microsemi, a wholly owned subsidiary of Microchip Technology Inc. All rights reserved. Microsemi and the Microsemi logo are registered trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.